

Shielding gas.

Gases for welding carbon and low-alloy steels.





Steel forms the largest and most widely used group of structural and engineering alloys with more steel being used in manufacturing than all other metals and alloys put together.

Steel is a term generally used to describe an extensive range of iron-carbon alloys. The carbon content may be up to 2% but the majority of steels contain less than 1%.

Simple steels, with carbon, silicon and manganese as the main alloying additions are often called carbon steels or carbon-manganese steels, whereas steels with small amounts of additional alloying additions such as chromium, nickel and molybdenum are called low-alloy steels. Low-alloy steels are used in a wide range of applications such as low and high temperature service, creep and wear resisting applications.

Improved performance for MAG welding.

Gases for MAG welding of carbon and low-alloy steels

	Thickness range	Penetration	Spatter control	Welding speed	Fillet shape	Finish
ARGOSHIELD® Light	1 to 8 mm	***	***	***	***	***
ARGOSHIELD® MCW	1 to 12 mm	**	***	***	***	***
ARGOSHIELD® Universal	4 to 13 mm	***	**	**	**	**
ARGOSHIELD® Heavy	4 to 13 mm	***	**	**	**	**
ARGOSHIELD® 52	11 to 13 mm	***	**	**	**	**
ARGOSHIELD® 40	1 to 8 mm	**	***	***	***	***
ARGOSHIELD® 54	1 to 11 mm	**	***	***	***	***
ARGOSHIELD® 100	1 to 13 mm	***	***	***	***	***
Carbon Dioxide	1 to 13 mm	***	**	**	**	**

The greater the number of stars, the better the gas performs.

MAG welding is the most common welding process used for welding carbon and low-alloy steels. The high productivity obtained through this process makes it ideally suited for the construction and manufacturing of steel structures and components.

Its versatility also allows it to be used either manually, automatically or robotically. The choice is determined by the complexity of the component to be welded, the skill of the workforce and production requirements.

Argon based gas mixtures are commonly used to weld carbon and low-alloy steels. These mixtures contain additions of active gases – oxygen and/or carbon dioxide – to improve welding performance. Helium may also be added, especially if high production rates are required. The amount of these active gases added depends on the material thickness, production performance required and welding method, be it manual, automatic or robotic.

ARGOSHIELD® Light

Gas code 060

Components: 3.1% oxygen, 5% carbon dioxide, balance argon



This three component shielding gas is designed predominantly for welding thinner materials. The low levels of carbon dioxide and oxygen in the weld reduce the risk of burning through and leaving holes in the weld area.

The addition of oxygen improves the flow of the molten weld metal producing flatter welds with lower levels of reinforcement. This can greatly reduce the need to machine or grind down the reinforcement, which is a known stress raiser, reducing production costs.

ARGOSHIELD® Light has excellent arc stability minimising the amount of spatter produced. Reduced spatter means less welding wire being wasted, as well as shorter clean up time – both again lowering production costs. This makes the product ideal for welding components that are painted or powder coated after welding.

The faster welding speeds achievable with this gas coupled with a low heat input also help to reduce welding distortion.


However, this product can suffer from lack of sidewall fusion and inter-run porosity when welding thicker materials.



ARGOSHIELD® MCW

Gas code 066

Components: 10% carbon dioxide, balance argon



ARGOSHIELD® MCW is a good general purpose shielding gas for use in dip, pulse and spray transfer. The amount of spatter and slag islands produced by this mixture is low, making it ideal for applications where minimum post weld cleaning is required, saving time and reducing the cost of manufacture. The low surface oxidation also makes it ideal for applications that require post weld painting.


Although suitable for a range of material thicknesses, care must be taken when welding above 8 mm thickness in spray transfer, as lack of sidewall fusion can be a problem.

Used in a wide range of industries from truck manufacture to ship building, it is ideal in applications where components are powder coat painted after welding.

ARGOSHIELD® Universal

Gas code 065

Components: 2.75% oxygen, 16% carbon dioxide, balance argon



A three component mixture designed for maximum performance. ARGOSHIELD® Universal has a large current/voltage operating envelope making it easier to set a good welding condition, giving it a high level of welder acceptance, reducing the instances of weld defects.

Ideal for manual, automatic and robotic applications, it is the most stable and fluid shielding gas of its type. This ensures low spatter levels along with good penetration and sidewall fusion, reducing weld defects and keeping component reject levels to a minimum.

ARGOSHIELD® Universal also produces smooth flat welds with low levels of reinforcement, wasting less welding wire than other mixtures. The fluid nature of the molten weld metal ensures good wetting action at the edges of the weld and the parent material, reducing the risk of stress defects occurring.


Welding speeds are high over a wide range of welding conditions, making ARGOSHIELD® Universal the first choice product when high levels of productivity and low levels of distortion are important.



ARGOSHIELD® Heavy

Gas code 122

Components: 18% carbon dioxide, balance argon



ARGOSHIELD® Heavy produces welds with very good penetration and sidewall fusion, especially when welding thicker materials. This reduces the number of defects in the weld, cutting down on rejected components. This mixture performs extremely well in both dip and spray but is on the upper limit of CO₂ content for pulse welding.

The high CO₂ content helps cope with surface contamination such as oil, moisture or rust, reducing pre-weld cleaning and thus reducing the cost of manufacture.

However, the higher CO₂ content produces more spatter and slag islands, which can add cost to the manufacturing process if clean, smooth weld areas are required. Welding sheet material is also more difficult with this gas, as the more fluid weld pool makes it easier to burn through.

ARGOSHIELD® 52

Gas code 070

Components: 25% carbon dioxide, balance argon




ARGOSHIELD® 52 is commonly used with most FCAW and MCAW wires. When using flux cored wires, it results in higher productivity due to faster welding speeds than Carbon Dioxide.

ARGOSHIELD® 52 also has a higher heat input efficiency with deep penetration welds. It is also excellent in dip transfer and pulse modes.

ARGOSHIELD® 40

Gas code 068

Components: 5% oxygen, balance argon



ARGOSHIELD® 40 is a 2 component mixture which has been specifically developed for MAG welding of carbon and alloy steels on thin material. This is because it reduces the risk of burning through and leaving holes in the weld area.

This mixture can be used manually or with robotic or automatic equipment. It is best suited for welding thicknesses between 0.7 and 6mm. However, it can be successfully used outside this range.


ARGOSHIELD® 40 has a very stable welding arc, it produces a fluid weld which will give faster welding speeds. This lowers production costs with reduced spatter and clean up times. The additional oxygen component flattens the weld and reduces surface tension.



ARGOSHIELD® 54

Gas code 071

Components: 1.5% oxygen, 7% carbon dioxide, balance argon




This 3 component shielding gas is designed predominantly for welding thinner materials making it ideal for applications where minimum post weld cleaning is required. This helps save time and results in a reduction in the cost of manufacture.

ARGOSHIELD® 54 can be used manually or with robotic or automatic equipment and is best suited for welding thicknesses between 0.7 and 8mm. However, it can be successfully used outside of this range but care must be taken as sidewall fusion can be a problem.

ARGOSHIELD® 100

Gas code 095

Components: 10% carbon dioxide, 25% helium, balance argon



This helium containing mixture has been developed primarily for use with automatic and robotic applications, as it is only mechanised production methods that can fully utilise the faster welding speeds achieved with this mixture. Faster welding speeds will enable more components to be produced in the same time when compared to other shielding gases.

Fast welding speeds are also beneficial in reducing distortion, cutting down on the number of rejected components.

This mixture produces a stable welding arc, which together with the higher thermal conductivity of helium creates a fluid, slow cooling weld pool that produces welds with low levels of defects such as porosity and lack of sidewall fusion.

Benefits for flux and metal cored welding.

Alloy flux cored and metal cored arc welding

	Thickness range	Penetration	Spatter control	Welding speed	Fillet shape	Finish
ARGOSHIELD® MCW	1 to 12 mm	***	***	***	***	***
ARGOSHIELD® Heavy	4 to 13 mm	**	**	**	**	**
ARGOSHIELD® 52	11 to 13 mm	**	**	**	**	**
Carbon Dioxide	1 to 13 mm	**	**	**	**	**

The greater the number of stars, the better the gas performs.

Flux cored arc welding and metal cored arc welding processes are similar to MAG welding, except that the welding wires are of a tubular construction containing flux powders and/or metal powders rather than being solid.

Consumable manufacturers blend their wires to suit one or two shielding gas mixtures; check which are recommended before commencing welding.

ARGOSHIELD® MCW

Gas code 066

Components: 10% carbon dioxide, balance argon




Generally recommended for use with metal cored wires. The relatively low level of carbon dioxide in the mixture produces fewer surface slag islands and lower oxide inclusions than shielding gases with higher carbon dioxide levels. This reduces post weld cleaning time and leads to improvements in productivity.

ARGOSHIELD® Heavy

Gas code 122

Components: 18% carbon dioxide, balance argon



Welding using this mixture results in very good penetration and sidewall fusion. This is particularly the case when welding thicker materials. As a result, using ARGOSHIELD® Heavy reduces the defects in the weld.

ARGOSHIELD® 52

Gas code 070

Components: 25% carbon dioxide, argon



For use with flux cored wires which are recommended for use with "mixed gas". In general it gives lower fume and spatter levels than pure carbon dioxide. Lower fume levels can improve the workplace environment as well as improve the wellbeing of the workforce.

Carbon dioxide

Gas code 081

Components: carbon dioxide



This gas is suitable for use with many brands and types of flux cored wire. Often suggested by flux cored wire manufacturers because of its lower price, CO₂ gives good penetration even when welding in position.

However, it also produces a less stable welding arc which can increase the amount of spatter and particulate fume. This can lead to an increase in the cost of post weld cleaning.



ARGOSHIELD®
MCW



Argon

High quality in TIG welding.

Gases for TIG welding

	Thickness range	Penetration	Spatter control	Welding speed	Fillet shape	Finish
Argon	1 to 8 mm	** *	***	** *	** *	** *
ALUSHIELD® Light	1 to 8 mm	***	***	** *	***	** *
ALUSHIELD® Universal	4 to 13 mm	***	***	** *	***	***
ALUSHIELD® Heavy	4 to 13 mm	***	***	***	***	***

The greater the number of stars, the better the gas performs.

TIG welding is less frequently used with carbon steels and is used more for welding low-alloy steels where high precision joints and excellent surface finish are more important than high productivity. Since the TIG process uses a non-consumable tungsten electrode, which is susceptible to damage by oxidising gases and is hydrogen sensitive, gases for TIG welding these steels are usually limited to inert mixtures.

Argon


Gas code 061
Component: argon



Argon is the most common gas for TIG welding both carbon and low alloy steels because of its versatility. The welding arc is very easy to initiate which makes it ideal for all types of arc initiation systems.

ALUSHIELD® Light

Gas code 079
Components: 27% helium, balance argon



The addition of helium to argon creates a more fluid weld pool which reduces porosity levels in the weld. The extra energy available from the helium also produces deeper penetration and better fusion, improving weld quality and reducing the risk of defects occurring.

Having a more fluid weld pool also helps to achieve faster welding speeds, so productivity rates are higher than with pure argon.

ALUSHIELD® Universal


Gas code 133
Components: 50% helium, balance argon



This higher helium mixture is best suited for use on thicker section materials to take advantage of the additional energy available. This helps improve penetration and fusion, producing welds with lower defects. It is widely used on automatic welding stations where high welding speeds are the primary concern.

ALUSHIELD® Heavy

Gas code 069
Components: 25% argon, balance helium



ALUSHIELD® Heavy results in welding speeds which can be 20 to 30% faster than Argon on 10mm thick materials.

The 75% helium content allows the mixture to provide the highest energy transfer when welding. This results in deep wide weld beads and reduces the chances of side wall fusion defects.

Getting ahead through innovation.

With its innovative concepts, BOC is playing a pioneering role in the global market. As a technology leader, it is our task to constantly raise the bar. Traditionally driven by entrepreneurship, we are working steadily on new high-quality products and innovative processes.

BOC offers more. We create added value, clearly discernible competitive advantages, and greater profitability. Each concept is tailored specifically to meet our customers' requirements – offering standardised as well as customised solutions. This applies to all industries and all companies regardless of their size.

If you want to keep pace with tomorrow's competition, you need a partner by your side for whom top quality, process optimisation, and enhanced productivity are part of daily business. However, we define partnership not merely as being there for you but being with you. After all, joint activities form the core of commercial success.

BOC – turning ideas into solutions.



Check out our YouTube video for tips on welding mild steel.

For more information contact the BOC Customer Engagement Centre on:

131 262

www.boc.com.au

<https://www.youtube.com/user/boclimited>

BOC Limited, ABN 95 000 029 729

10 Julius Avenue, North Ryde, NSW 2113, Australia

BOC is a trading name of BOC Limited, a Member of The Linde Group. © BOC Limited 2015. Reproduction without permission is strictly prohibited. Details given in this document are believed to be correct at the time of printing. Whilst proper care has been taken in the preparation, no liability for injury or damage resulting from its improper use can be accepted.